

QuickSeam™ Cover Strip



1. Description

The Firestone QuickSeam™ Cover Strip is a 152 mm (6") wide semi-cured EPDM strip laminated to a QuickSeam tape. The strip is used to cover and seal butt-joined Firestone RubberCover™ EPDM membranes.

2. Preparation

The RubberCover™ EPDM surfaces must be prepared with QuickPrime™ Plus, using a QuickScrubber™ tool. Use of other products is not allowed. Restore the product to room temperature prior to use if exposed to temperatures below 15°C for prolonged periods.

3. Application

Place the roll of cover strip on the membrane, positioned so it unrolls from the top of the roll (release paper will be on top) and center the cover strip over the exposed membrane edge(s). Unroll the cover strip onto the clean and primed surface. Advance the roll keeping the strip centered over the membrane edge(s) and peel the release paper as you apply the strip.

4. Coverage

In accordance with length of seam to be covered. Adjoining QuickSeam Cover Strips require an overlap of 5-25 mm and a QuickSeam Corner Flashing cover patch.

5. Characteristics

Technical		
	EPDM Flashing	QuickSeam Tape
• Base	EPDM	Rubber polymers
• Color	Black	Black
• Solvents	None	None
• Solids	100%	98%
• State	Semi-cured	Cured
• Thickness	1.02 mm	0.89 mm
• Width	152 mm	156 mm

6. Packaging / Storage / Shelf Life

Packaging	7.62 m (25') rolls, 8 rolls per carton
Part number	W56RAC1693

Storage: Store in original unopened containers at temperatures between 15°C and 25°C, in a well-ventilated place. Keep the material dry and out of direct sunlight until ready for application.

Shelf Life: 12 months can be expected if stored in above-mentioned conditions. Verify production date on each roll. Shelf life will be reduced if exposed to higher temperatures. Shelf life information is only a recommendation and not a fact of life. The real expiration date highly depends on the history of storage and handling of the accessories.

7. Precautions

Refer to Safety Data Sheet.

This document replaces any other document published previous. This sheet is meant to highlight Firestone product information based on latest knowledge and experience and is subject to change without notice (check the Firestone website for latest document version). Above mentioned values are based on tested samples and may vary within applicable tolerances. Firestone takes responsibility for furnishing quality materials which meet published Firestone product specifications. No Firestone representative is authorized to vary this disclaimer.